

Est. 1956
THE CLEAN AIR PEOPLE

Description

The TFS filter made of Aluminum fly screen frame with G2 efficiency media, held with rubber spline to ensure good sealing between frame and media. They also can be made to different sizes based on requirement. For larger filters cross brace is placed on air leaving side to prevent rattle and any distortion.

The TFS Panel Filters are available in standard and non-standard sizes with efficiencies suited for all residential and commercial applications. The TFS Panel Filters are suited to non-critical applications or as a pre-filter to extend the life of the secondary filter. The TFS Panel Filter is easily made-up in banks with the use of the appropriate type of holding frame.



Maintenance

The TFS Panel Filter can be hosed from the clean air side with care. Before installing back into frames or slides the media should be dry. Also check media for wear or damage and replace filter pad if necessary.

PERFORMANCE DATA				
- TFS PANEL FILTER -				
Product Code	Nominal Size (mm)	Airflow Capacity (l/sec)	Initial Resistance (Pascals)	Efficiency
BG-01	495 x 395 x 9	350	27	G2
BG-02	495 x 495 x 9	440	27	G2
BG-03	622 x 395 x 9	440	27	G2
BG-04	622 x 495 x 9	555	27	G2
BG-05	749 x 495 x 9	665	27	G2
BG-06	595 x 595 x 9	640	27	G2
BG-07	NON-STD	?	?	?
BG-08	595 x 295 x 9	310	27	G2