

Est. 1956
THE CLEAN AIR PEOPLE

Description

The disposable V-Form Panel Filters are available in standard and non-standard sizes with efficiencies of G4 or F5 to EN 779 and are available in a range of standard and non-standard sizes of nominal 48 and 95mm thicknesses. The V-Form Panel Filters are suited to non-critical applications or as a pre-filter to extend the life of the secondary filter. The V-Form Panel Filter is easily made-up in banks with the use of the appropriate Ludwig type clips or c/clip holding frame.

Construction

V-Form Panel Filters come in a metal outer frame with galvanised mesh each side of the filter medium. The corners are notched, and the frame is riveted securely. The filter medium is available in a G4 as standard. Manufactured from bonded synthetic fibres, other efficiencies are available upon request. V-Form extended surface panel filters are suitable as a primary filter to meet AS 1668.2 and can be installed in universal holding frames, side access applications and similar existing hardware. They may be used as pre-filters to extend the life of Multi-Wedge, Multi-pocket, Multi-Vee Ridge, Rainbow Cells.

Options

- Non Standard Sizes Readily Available
- Available in 304 & 316 Grade Stainless Steel



PERFORMANCE DATA

- Disposable V/Forms -

Product Code	Nominal Size (mm)	Airflow Capacity (l/sec)	Initial Resistance (Pascals)	Efficiency
FAN2-01	495 x 395 x 48	350	30	G4
FAN2-02	495 x 495 x 48	440	30	G4
FAN2-03	622 x 395 x 48	440	30	G4
FAN2-04	622 x 495 x 48	555	30	G4
FAN2-05	749 x 495 x 48	665	30	G4
FAN2-06	595 x 595 x 48	640	30	G4
FAN2-08	595 x 295 x 48	310	30	G4
FAN4-01	495 x 395 x 95	350	20	G4
FAN4-02	495 x 495 x 95	440	20	G4
FAN4-03	622 x 395 x 95	440	20	G4
FAN4-04	622 x 495 x 95	555	20	G4
FAN4-05	749 x 495 x 95	665	20	G4
FAN4-06	595 x 595 x 95	640	20	G4
FAN4-08	595 x 295 x 95	310	20	G4